

Description	Beger Thinner #M-22, solvent thinner for paint dilution and paint equipments cleaning.		
Properties for Use	Beger Thinner #M-22 is thinner formulated for dilute and join Polyurethane.		
Film Thickness and Spreading Rate	Minimum	Maximum	Typical
* Dry film thickness (microns)	0	0	0
* Wet film thickness (microns)	0	0	0
* Theoretical coverage rate (m ² /U.S.Gallon/coat)	0	0	0
Physical Properties			
* Vehicle type	: Thinner		
* Finish	: Matt		
* Colour	: Water Clear		
* Viscosity (@25'C)	: -		
* Specific gravity	: -		
* Solid by volume	: -		
* Solid by weight	: -		
* Dry time (@25'C, 30 mm.DFT)	: -		
Touch dry	: -		
Recoat	: -		
Dry to handle	: -		
* Flash point	: 18 - 22'C		
Application Method			
* Tool	: Brush, roller or spray gun.		
* Thinner	: -		
* Condition during application	: Application by roller and brush : dilute with 10 - 15% Beger Thinner #M-22 by volume. : Application by spray gun : dilute with 15 - 20% Beger Thinner #M-22 by volume. : The temperature of the substrate should be minimum +10'C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate. Good ventilation is required in confined areas to ensure proper drying.		
Storage			
	: Handle with care. Stir well before and occasionally during application. : The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. : Containers must be kept tightly closed. : 12 months at ambient.		
Health and safety			
	: Use under well ventilated conditions. : Do not breathe or inhale mist. : Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. : Eyes should be well flushed with water and medical attention sought immediately.		
Precaution	: Keep out of reach of children.		
Reference Standard	: -		
Packing Size	: 1/4 Gallon, 1 Gallon.		

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.