

<b>Description</b>	Beger One is matt interior paint and primer in one, which is exceptional hide with Max-Cover Titanium technology combined with acrylic resin from Germany's technology, consequently. It is high concentrate paint that giving a perfect finish in just one coat while conventional paint need 3 times. It has helped to save your time, labor cost and paints. Furthermore it has silver iron inside to ant-microbial growth activity and very mild odor therefore can move inside just 5 minutes after paint dry.		
<b>Feature and Benefits</b>	* Matt interior. * Excellent hiding. * Easy to application by high quality roller. * Highly scrub resistance.	* Give a perfect finish in just one coat. * Low VOCs, low odor, environmental friendly. * Anti-microbial.	
<b>Properties for Use</b>	Beger One use as a interior top coat on cured cement, gypsum.		
<b>Film Thickness and Spreading Rate</b>	Minimum 80 170 7	Maximum 100 210 8.5	Typical 0 0 Actual consumption rate depends on application method and surface condition.
<b>Physical Properties</b>	* Vehicle type : Acrylic Emulsion * Finish : Matt * Colour : According to the "Beger One" * Specific gravity : 1.44-1.49 * Solid by volume : 56.5-59.0 * Dry time (@25'C, 30 mm.DFT) Touch dry : 20 minutes Dry to handle : 45-60 minutes		
<b>Application Method</b>	* Tool : High quality roller. * Thinner : Not recommended diluted. * Condition during application : The moisture content in the concrete should not exceed 14%. : Concrete and masonry cure at least 30 days before coating.		
<b>Application System</b>	* Surface preparation : Surface should be dry and clean. : Remove completely all dirt, grease, oil, water or any contaminated by washing surface with suitable cleaner. : Repair all surface imperfections. Before application, fill and seal hairline cracks by working a generous amount of material into void. Cracks and gaps wider than 2.0 - 10.0 mm. should be filled with acrylic sealant. Use Beger Acrylic Wall Filler #F-200 for cracks and gaps with less than 0.3 - 1.0 mm. width. : Surface with fungus, mold and mildew growth must be cleaned off and follow by the treatment of fungicidal wash Beger MouldFree #M-001. * Typical paint system : New masonry substrate * Primer and top coat : Beger One 1 coat If the surface's moisture content more than 14%, apply Beger Multi-Purpose Primer #B-1900 1 coat : Lightweight concrete and pre-cast walls * Primer : Beger Skim Cote #101 and 1 coat : Beger Cool All Plus Alkali Resisting Primer #5000 or 1 coat : Beger Skim Cote #102 without primer 1 coat * Top coat : Beger One 1 coat : Old masonry or deteriorated surfaces * Primer and top coat : Beger One 1 coat In case chalky conditions, apply Beger Multi-Purpose Primer #B-1900 1 coat : Painted surfaces, in case light shade of Beger One over painted deep shade wall, 2nd coat of Beger One must be applied to cover that area. 1 coat * Primer and top coat : Beger One 1 coat		
<b>Storage</b>	: The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. : Containers must be kept tightly closed. : 6-12 months at ambient.		
<b>Health and safety</b>	: Use under well ventilated conditions. : Do not breathe or inhale mist. : Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. : Eyes should be well flushed with water and medical attention sought immediately.		
<b>Precaution</b>	: Keep out of reach of children.		
<b>Reference Standard</b>	: TIS 2321-2549 Weather Resistant Emulsion Paint for Interior.		
<b>Packing Size</b>	: 3 litres and 8 litres.		

**DISCLAIMER**

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.