



BEGER CERAMICCLEAN ALKALI RESISTANCE PRIMER #1200

Acrylic Alkali Resisting Primer : Professional Interior Primer

Description	<p>Beger CeramicClean Alkali Resistance Primer #1200 is formulated from high performance 100% acrylic binder. It is a premium quality, fast curing; flat finish primer specially formulated to provide a superior prime coat over interior surfaces such as new gypsum wallboard and textured sheetrock. It equalizes the absorption rate of topcoat paints over a variety of surfaces with different porosities, and helps to eliminate decorating problems over substrate.</p> <p>No added lead and no added mercury for health and environmental safe.</p>		
Feature and Benefits	<ul style="list-style-type: none"> * Easy to apply, give smooth appearance. * Good opacity and can be used over a wide variety of substrates. * Increase thermal resistance to paint film, to reduce energy coat compared to traditional. 		
Properties for Use	<p>Beger CeramicClean Alkali Resistance Primer #1200 is ideal for use on most types of interior masonry surfaces including new concrete, cement, asbestos sheet, etc.</p>		
Film Thickness and Spreading Rate	Minimum	Maximum	Typical
* Dry film thickness (microns)	35	40	0
* Wet film thickness (microns)	0	0	0
* Theoretical coverage rate (m ² /U.S.Gallon/coat)	30	40	Actual coverage may vary depending on substrate and application method.
Physical Properties	<ul style="list-style-type: none"> * Vehical type : Water-Based Primer * Finish : Matt * Colour : White * Solid by volume : 38 - 42% * Dry time (@25°C, 30 mm.DFT) <ul style="list-style-type: none"> Touch dry : 30 minutes Recoat : 2 hours Dry to handle : - * Flash point : More than 65°C 		
Application Method	<ul style="list-style-type: none"> * Tool : Brush, roller or spray gun. * Thinner : Clean water * Condition during application : The moisture content in the concrete should not exceed 14% (by weight). : Concrete and masonry cure at least 30 days before coating. : Application by brush : dilute with 10% clean water by volume. : Application by roller : dilute with 5 - 10% clean water by volume. 		
Application System	<ul style="list-style-type: none"> * Surface preperation : Surface should be dry and clean. : Remove completely all dirt, grease, oil, water or any contaminated by washing surface with suitable cleaner. : Repair all surface imperfections. Before application, fill and seal hairline cracks by working a generous amount of material into void. Cracks and gaps wider than 0.3 mm. should be filled with acrylic sealant. Use Beger Acrylic Wall Filler #F-200 for cracks and gaps with less than 0.3 mm. width. : Surface with fungus, mold and mildew growth must be cleaned off and follow by the treatment of fungicidal wash Beger Mould Wash #3600. * Typical paint system : New masonry substrate <ul style="list-style-type: none"> * Beger CeramicClean Alkali Resistance Primer #1200 1 - 2 coats * Beger CeramicClean 100% Acrylic Emulsion Paint 2 coats : Previously painted surfaces <ul style="list-style-type: none"> * Beger Multi-Purpose Primer #B-1900 1 coat * Beger CeramicClean Alkali Resistance Primer #1200 1 - 2 coats * Beger CeramicClean 100% Acrylic Emulsion Paint 2 coats 		
Storage	<ul style="list-style-type: none"> : The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away form source of heat an ignition. : Containers must be kept tightly closed. : 12 months at ambient. : Handle with care. Mix thoroughly before use. 		
Health and safety	<ul style="list-style-type: none"> : Use under well ventilated conditions. : Do not breathe or inhale mist. : Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. : Eyes should be well flushed with water and medical attention sought immediately. 		
Precaution	<ul style="list-style-type: none"> : Keep out of reach of children. 		
Reference Standard	: -		
Packing Size	: 1 Gallon, 5 Gallons.		

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, We cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice. Beger CeramicClean Alkali Resistance Primer #1200

